

We make a colorful world

Series 900 系列

Face Vinyl: polymeric calendered films are produced under **ISO-9001 2008** certification.

Thickness: 80 micron **Type:** Matt **Outdoor durability:** long term application.

Substrate: Glossy Surface, Glass, Acrylic Sheets, Polycarbonate Sheets, Metal & Flex Face, etc.

Standard size: Adhesive color films 92cm(36") / 122cm(48") x 10yds / 20yds / 30yds / 50yds
 UV protection films 97cm / 130cm / 155cm x 50yds

面 膜：**ISO-9001 2008** 超頂級高分子可塑化膠膜。

室外使用：耐老化，龜裂，抗紫外線，戶外長期耐候品質保證。

適用底材：光滑表面底材，如燈箱軟材、玻璃、壓克力、PC板及金屬等。

UV保護膜：適用噴畫圖面冷裱，廣告招牌版面保護，可提升色彩耐候功效一倍以上。

標準尺寸：彩色膠膜 92cm(36") / 122cm(48") x 10yds / 20yds / 30yds / 50yds
 UV保護膜 97cm / 130cm / 155cm x 50yds

規格值 / SPECIFICATION

物性 / Property	數 值 / Value	試驗方法 / Method
厚度 Thickness(mm)	0.08 ± 0.012mm	ASTM D - 1593
拉力強度 Tensile Strength (Kg/mm ²)	MD : 2.9 (min.) CD : 2.6 (min.)	ASTM D - 882
延伸率 (%) Elongation	MD : 168 (min.) CD : 240 (min.)	ASTM D - 882
撕裂強度 Tearing Strength (Kg/mm)	MD : 8.0 (min.) CD : 7.5 (min.)	ASTM D - 1004
尺寸安定性 (%) Dimensional Stability	11 (max.)	ASTM D - 1204 100°C x 30 min / oven



	9710		9721		9731		9751
	9711		9723		9732		9755
	9712		9724		9735		9757
	9713		UV Film 保護膜		9736		9758
	9714		9725		9737		9759
	9715		9726		9739		9760
	9716		9727		9740		9761
	9717		9728		9741		9766
	9718		9729		9747		9767
	9719		9730		9750		9768
	9720		9703		9705		9707
	9701		9704		9706		9708